

www.sughrue.com



JC14 Rec'd PGT/PTO 19 DEC 2001

December 19, 2001

BOX PCT

Commissioner for Patents
Washington, D.C. 20231

PCT/JP00/04078
-filed June 22, 2000

Re: Application of Takayuki ARAKI, Nobuhiro HIRANO and Noritoshi OKA
FLEXIBLE FLUORINE-CONTAINING MATERIAL HAVING HEAT
RESISTANCE AND NON-TACKINESS
Assignee: **DAIKIN INDUSTRIES, LTD.**
Our Ref: Q67743

Dear Sir:

The following documents and fees are submitted herewith in connection with the above application for the purpose of entering the National stage under 35 U.S.C. § 371 and in accordance with Chapter II of the Patent Cooperation Treaty:

- ☒ an executed Declaration and Power of Attorney.
- ☒ an English translation of the International Application.
- ☒ an executed Assignment and PTO 1595 form.
- ☒ International Search Report, Information Disclosure Statement, PTO Form 1449 with references.
- ☒ Notification Concerning Submission or Transmittal of Priority Document.
- ☒ a Preliminary Amendment

It is assumed that copies of the International Preliminary Examination Report, and any Articles 19 and 34 amendments as required by § 371(c) will be supplied directly by the International Bureau, but if further copies are needed, the undersigned can easily provide them upon request.

The Government filing fee, after entry of the Preliminary Amendment, is calculated as follows:

Total claims	<u>14</u>	-	20	=	<u> </u>	x \$18.00 =	<u>\$0.00</u>
Independent claims	<u>1</u>	-	3	=	<u> </u>	x \$84.00 =	<u>\$0.00</u>
Base Fee							\$890.00

TOTAL FILING FEE	\$890.00
Recordation of Assignment	\$ 40.00
TOTAL FEE	\$930.00

10/018345

JC13 Rec'd PCT/PTO 19 DEC 2001



Checks for the statutory filing fee of \$890.00 and Assignment recordation fee of \$40.00 are attached. You are also directed and authorized to charge or credit any difference or overpayment to Deposit Account No. 19-4880. The Commissioner is hereby authorized to charge any fees under 37 C.F.R. §§ 1.16, 1.17 and 1.492 which may be required during the entire pendency of the application to Deposit Account No. 19-4880. A duplicate copy of this transmittal letter is attached.

Priority is claimed from:

<u>Country</u>	<u>Application No</u>	<u>Filing Date</u>
Japan	186792/1999	June 30, 1999

Respectfully submitted,

SUGHRUE MION, PLLC
2100 Pennsylvania Avenue, N.W.
Washington, D.C. 20037-3213
Telephone: (202) 293-7060
Facsimile: (202) 293-7860
AJR/tmm
Date: December 19, 2001

Abraham J. Rosner
Registration No. 33,276

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of

Takayuki ARAKI, et al.

Appln. No.: National Stage of PCT/JP00/04078

Confirmation No.: Not Yet Assigned

Group Art Unit: Not Yet Assigned

Filed: December 19, 2001

Examiner: Not Yet Assigned

For: FLEXIBLE FLUORINE-CONTAINING MATERIAL HAVING HEAT RESISTANCE
AND NON-TACKINESS

PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, D.C. 20231

Sir:

Prior to examination, please amend the above-identified application as follows:

IN THE CLAIMS:

Please enter the following amended claims:

3. (Amended) The flexible fluorine-containing material of Claim 1, wherein said weight ratio (a)/(b) is 20/80 to 99/1.

4. (Amended) The flexible fluorine-containing material of Claim 1, wherein the elastomeric fluorine-containing polymer chain segment A contained in the fluorine-containing multi-segment polymer (a) is non-crystalline and has a glass transition temperature of not more than 25°C.

PRELIMINARY AMENDMENT - Q67743

5. (Amended) the flexible fluorine-containing material of Claim 1, wherein the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is a polymer chain having a crystalline melting point or glass transition temperature of not less than 150°C.

7. (Amended) The flexible fluorine-containing material of Claim 1, wherein the elastomeric fluorine-containing polymer chain segment A contained in the fluorine-containing multi-segment polymer (a) is a polymer chain comprising 50 to 85% by mole of tetrafluoroethylene and 15 to 50 % by mole of perfluoro(alkyl vinyl ether) and/or hexafluoropropylene.

8. (Amended) The flexible fluorine-containing material of Claim 1, wherein the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is a polymer chain comprising more than 85% by mole and not more than 100 % by mole of tetrafluoroethylene and 0 % by mole or less than 15 % by mole of a compound of the formula (1):



wherein R_f^1 is CF_3 or OR_f^2 is a perfluoroalkyl group having 1 to 5 carbon atoms.

9. (Amended) The flexible fluorine-containing material of Claim 1, wherein the fluorine-containing resin (b) is one or more members selected from perfluoro fluorine-containing resins.

PRELIMINARY AMENDMENT - Q67743

11. (Amended) The flexible -containing material of Claim 1, wherein a proportion of the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is not more than 25 % by weight based on the whole segment polymer (a).

Please add the following new claims:

12. (New) The flexible fluorine-containing material of Claim 4, wherein the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is a polymer chain having a crystalline melting point or glass transition temperature of not less than 150°C.

13. (New) The flexible fluorine-containing material of Claim 7, wherein the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is a polymer chain comprising more than 85 % by mole and not more than 100 % by mole of tetrafluoroethylene and 0 % by mole or less than 15 % by mole of a compound of the formula (1):



wherein R_f^1 is CF_3 or OR_f^2 , in which R_f^2 is a perfluoroalkyl group having 1 to 5 carbon atoms.


14. (New) The flexible fluorine-containing material of Claim 13, wherein the fluorine-containing resin (b) is one or more members selected from perfluoro fluorine-containing resins.

PRELIMINARY AMENDMENT - Q67743

REMARKS

Entry and consideration of this Amendment is respectfully requested.

Respectfully submitted,



Abraham J. Rosner
Registration No. 33,276

SUGHRUE MION, PLLC
2100 Pennsylvania Avenue, N.W.
Washington, D.C. 20037-3213
Telephone: (202) 293-7060
Facsimile: (202) 293-7860
DM/tmm
Date: December 18, 2001

APPENDIX
VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE CLAIMS:

The claims are amended as follows:

3. (Amended) The flexible fluorine-containing material of [Claim 1 or 2] Claim 1, wherein said weight ratio (a)/(b) is 20/80 to 99/1.

4. (Amended) The flexible fluorine-containing material of [any of Claims 1 to 3] Claim 1, wherein the elastomeric fluorine-containing polymer chain segment A contained in the fluorine-containing multi-segment polymer (a) is non-crystalline and has a glass transition temperature of not more than 25°C.

5. (Amended) the flexible fluorine-containing material of [any of Claims 1 to 4] Claim 1, wherein the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is a polymer chain having a crystalline melting point or glass transition temperature of not less than 150°C.

7. (Amended) The flexible fluorine-containing material of [any of Claims 1 to 6] Claim 1, wherein the elastomeric fluorine-containing polymer chain segment A contained in the fluorine-containing multi-segment polymer (a) is a polymer chain comprising 50 to 85% by mole of tetrafluoroethylene and 15 to 50 % by mole of perfluoro(alkyl vinyl ether) and/or hexafluoropropylene.

PRELIMINARY AMENDMENT - Q67743

8. (Amended) The flexible fluorine-containing material of [any of Claims 1 to 7] Claim 1, wherein the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is a polymer chain comprising more than 85% by mole and not more than 100 % by mole of tetrafluoroethylene and 0 % by mole or less than 15 % by mole of a compound of the formula (1):



wherein R_f^1 is CF_3 or OR_f^2 is a perfluoroalkyl group having 1 to 5 carbon atoms.

9. (Amended) The flexible fluorine-containing material of [any of Claims 1 to 8] Claim 1, wherein the fluorine-containing resin (b) is one or more members selected from perfluoro fluorine-containing resins.

11. (Amended) The flexible -containing material of [any of Claims 1 to 10] Claim 1, wherein a proportion of the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is not more than 25 % by weight based on the whole segment polymer (a).

Claims 12-14 are added as new claims.

- 1 -

DESCRIPTION

FLEXIBLE FLUORINE-CONTAINING MATERIAL HAVING HEAT RESISTANCE AND NON-TACKINESS

5

TECHNICAL FIELD

The present invention relates to a fluorine-containing material having heat resistance and non-tackiness while having flexibility.

10

BACKGROUND ART

Fluorine-containing materials such as fluorine-containing resins and fluorine-containing rubbers are used as various starting materials in various fields by utilizing specific properties thereof.

15 Particularly the fluorine-containing materials play an important role in the field of OA equipment.

In that field, hitherto a urethane rubber, EP rubber, silicone rubber and the like have been used for rolls for printing machine and platen rolls. Also a silicone rubber roll, a fluorine-containing rubber
20 roll and the like are known as a fuser roll for electrophotographic copying machine. However in those rolls, even in case of use of a toner having releasing property, since releasing property (non-tackiness against toner) is not enough, a non-elastic roll coated with a fluorine-containing resin, an elastic roll covered with a shrinkable fluorine-
25 containing resin tube on its surface, or the like has been proposed. Further there have been proposed an elastic roll obtained by coating a mixture of fluorine-containing rubber and fluorine-containing resin

powder and then baking to form a fluorine-containing resin powder layer on the surface of roll (JP-B-1-36622), a roll obtained by coating a fluorine-containing rubber and fluorine-containing resin powder, baking and then further coating a fluorine-containing resin powder to form a
5 fluorine-containing resin layer (JP-B-6-100876), and the like roll.

In fixing operation of electrophotographic copying machine, coating of a releasing oil, generally a silicone oil on a fuser roll is carried out to improve releasing property of the fuser roll. In that case, in order to prevent a silicone oil from permeating inside the fuser roll and causing
10 swelling of the roll, there have been proposed a fuser roll obtained by covering a shrinkable fluorine-containing resin tube on an elastic roll or a fuser roll provided with a silicone rubber layer, a fluorine-containing rubber layer or a fluorosilicone rubber layer and a silicone rubber layer in that order on its metallic core roll as described in JP-A-1-205188, etc.

Also in JP-A-62-285839, the inventors of the present
15 invention proposed an elastic roll obtained by forming, on its metallic core roll, a layer of a heat resistant elastomer material impregnated and integrated with fibrillated polytetrafluoroethylene (PTFE), particularly stretched porous polytetrafluoroethylene.

On the other hand, in the roll for printing machine and platen roll which are produced by using a urethane rubber, EP rubber or silicone rubber, elasticity of the roll is good, but releasing property cannot always be said to be good. For that reason, there were problems that troubles such as adherence of toner, contamination of printed
25 matters due to adherence of paper powder and winding of paper on a roll occurred.

Particularly in case of the fuser roll for electrophotographic

copying machine, a non-elastic roll coated with a fluorine-containing resin such as PTFE or PFA (copolymer of tetrafluoroethylene and perfluoro(alkyl vinyl ether)) has a defect that the roll has no elasticity, and a roll obtained by covering a surface of elastic roll with a shrinkable
5 fluorine-containing resin tube is not always satisfactory from the viewpoint of surface elasticity since the fluorine-containing resin is hard and small in elongation. Further an elastic roll having a fluorine-containing resin powder layer on its surface (formed by powder coating of PFA, etc.) is good in elasticity and releasing property at an initial stage
10 of its use, but since the fluorine-containing resin powder on its surface is easily peeled or separated, a life of the releasing property is short and further in application for a fuser roll in which its temperature becomes as high as 150° to 200°C, heat resistance of the roll is not enough. Particularly since the fluorine-containing rubber component is
15 deteriorated and strength thereof is decreased, durability of the roll is lowered.

Also as described in JP-A-1-205188, etc., with respect to the roll having a silicone rubber layer on a fluorine-containing rubber layer or fluorosilicone rubber layer, strength of the silicone rubber layer on
20 the roll surface is insufficient. If an amount of a filler is increased to increase the strength, releasing property is lowered. Further since an adhesive strength between the silicone rubber layer and the fluorine-containing rubber layer or fluorosilicone rubber layer is not enough, there is a problem that coating of a silicone oil and fixing operations are
25 carried out repeatedly, thereby causing cracking on the surface silicone rubber layer and peeling thereof in the worst case. Further in application for a fuser roll in which its temperature becomes as high as

150° to 200°C, the surface silicone rubber layer and the inside fluorine-containing rubber layer or fluorosilicone rubber layer are deteriorated and abraded due to lowering of strength since heat resistance thereof is insufficient.

5 Also the elastic roll disclosed in JP-A-62-285839 is very excellent in releasing property and good in affinity and anti-swelling property with a silicone oil, but is poor in elastic properties, particularly elasticity recovering ability. Further the elastic roll is poor in heat conductivity and has a problem that its surface temperature is lowered
10 particularly at the time of copying continuously.

In recent years, in a copying machine, the tendency is toward color printing and higher copying speed, and thus a surface material for rolls of fixing part which has more flexibility, heat resistance and non-tackiness is demanded.

15 In LBP having a tendency toward color printing, high quality image and high speed, a toner itself also has a tendency of multi-colors and low viscosity. From the viewpoint of prevention of offsetting, more non-tackiness is also demanded on a material to be used on a surface of the fuser roll.

20 An object of the present invention is to provide a flexible fluorine-containing material which can cope with the above-mentioned problems in the field of OA equipment and naturally can be applied on various products, parts and coating in other fields.

25 The present inventors have found that a specific fluorine-containing multi-segment polymer having an elastomeric fluorine-containing polymer chain segment capable of giving flexibility to the whole polymer and a non-elastomeric fluorine-containing polymer chain

segment is suitable for applications where heat resistance, flexibility and non-tackiness are demanded, and also have found that the above-mentioned problematic points can be further improved by a combination of the specific fluorine-containing multi-segment polymer and a specific
5 fluorine-containing resin.

The flexible fluorine-containing material can be preferably used particularly as a material for rolls of OA equipment to be used for electronically fixing and photo-sensing applications. Particularly by using on a fuser roll, excellent fixing property, color developing property,
10 oil resistance, non-tackiness against toner and releasability of a paper can be exhibited and further heat resistance, non-tackiness, durability and abrasion resistance can be given to the surface of the roll.

DISCLOSURE OF INVENTION

15 The present invention relates to a flexible fluorine-containing material which comprises (a) a fluorine-containing multi-segment polymer having an elastomeric fluorine-containing polymer chain segment A and a non-elastomeric fluorine-containing polymer chain segment B in which the elastomeric fluorine-containing polymer chain
20 segment A comprises not less than 90 % by mole of perhaloolefin units and (b) a fluorine-containing resin having a crystalline melting point or glass transition temperature of not less than 150°C, in which a weight ratio (a)/(b) is 1/99 to 99/1.

It is preferable that the elastomeric fluorine-containing
25 polymer chain segment A contained in the fluorine-containing multi-segment polymer (a) is non-crystalline and has a glass transition temperature of not more than 25°C and that the elastomeric fluorine-

containing polymer chain segment A is a polymer chain comprising 50 to 85 % by mole of tetrafluoroethylene and 15 to 50 % by mole of perfluoro(alkyl vinyl ether) and/or hexafluoropropylene.

It is preferable that the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is a polymer chain having a crystalline melting point or glass transition temperature of not less than 150°C, particularly not less than 250°C and that the non-elastomeric fluorine-containing polymer chain segment B is a polymer chain comprising more than 85 % by mole and not more than 100 % by mole of tetrafluoroethylene and 0 % by mole or less than 15 % by mole of a compound of the formula (1):



wherein R_f^1 is CF_3 or OR_f^2 , in which R_f^2 is a perfluoroalkyl group having 1 to 5 carbon atoms.

Particularly it is preferable that a proportion of the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is not more than 25 % by weight based on the whole segment polymer (a).

On the other hand, it is preferable that the above-mentioned fluorine-containing resin (b) is a fluorine-containing resin having a crystalline melting point or glass transition temperature of not less than 250°C and further that the fluorine-containing resin (b) is one or more members selected from perfluoro fluorine-containing resins, particularly polytetrafluoroethylene (PTFE), tetrafluoroethylene/perfluoro(alkyl vinyl ether) copolymer (PFA), tetrafluoroethylene/hexafluoropropylene

copolymer (FEP) and tetrafluoroethylene/hexafluoropropylene/perfluoro(alkyl vinyl ether) copolymer (EPA).

The preferable weight ratio (a)/(b) is 40/60 to 99/1.

5

BEST MODE FOR CARRYING OUT THE INVENTION

First the fluorine-containing multi-segment polymer which is the component (a) of the present invention is explained below.

It is important that the fluorine-containing multi-segment
10 polymer contains, in one molecule thereof, the elastomeric fluorine-containing polymer chain segment A (hereinafter referred to as "elastomeric segment A") and the non-elastomeric fluorine-containing polymer chain segment B (hereinafter referred to as "non-elastomeric segment B") which are bonded in a blocked or grafted form.

15 In the present invention, for bonding the elastomeric segment A to the non-elastomeric segment B by blocking or grafting to obtain the fluorine-containing multi-segment polymer, various known processes can be adopted. Among them, a process for preparing a blocked fluorine-containing multi-segment polymer which is disclosed in JP-B-
20 58-4728, etc., a process for preparing a grafted fluorine-containing multi-segment polymer which is disclosed in JP-A-62-34324, and the like process can be adopted preferably.

Particularly preferred is the blocked fluorine-containing multi-segment polymer synthesized through a so-called iodine
25 transferring polymerization method which is disclosed in JP-B-58-4728 and Kobunshi Ronbunshu (Vol. 49, No. 10, 1992) from the viewpoint that a segmenting ratio (blocking ratio) is high and a uniform and

regular segment polymer can be obtained.

On the other hand, in case of a simple mixture of an elastomeric fluorine-containing polymer and non-elastomeric fluorine-containing polymer, generally mechanical properties (particularly at
5 high temperature) become insufficient and lowering of abrasion resistance, flexibility and durability arises though it depends on kind, miscibility and compatibility of the respective polymers to be mixed.

On the contrary, when the fluorine-containing resin is mixed to the multi-segment polymer prepared by bonding the elastomeric
10 segment A and the non-elastomeric segment B by blocking or grafting like the present invention, heat resistance, mechanical properties (particularly at high temperature), etc. are enhanced more and also in case of use for rolls, heat resistance, durability and abrasion resistance can be improved more effectively as compared with the above-mentioned
15 simple mixture of an elastomeric fluorine-containing polymer and non-elastomeric fluorine-containing polymer.

Further a rubber roll provided with a layer of fluorine-containing thermoplastic rubber having an elastomeric fluorine-containing polymer chain segment containing vinylidene fluoride as a
20 main component on its outer surface has been proposed (Utility Model Publication JU-B-2-15873). However though the fluorine-containing segment polymer is used, heat resistance and non-tackiness are not enough because the elastomeric fluorine-containing polymer chain segment does not contain a perhaloolefin unit as a main component.

25 The present inventors have further found that in the iodine transferring polymerization method, when not less than 90 % by mole of perhaloolefin units are contained as a recurring unit in the elastomeric

segment A, a block copolymerization reaction with a monomer for the non-elastomeric segment B proceeds regularly and uniformly and it is possible to largely decrease an amount of unintended products such as a molecule comprising only the elastomeric fluorine-containing polymer chain segment which is not bonded to the non-elastomeric component and the non-elastomeric fluorine-containing polymer chain segment having a low molecular weight even if a bonding occurs. The inventors also have found that the flexible fluorine-containing material of the present invention produced by mixing the thus obtained fluorine-containing multi-segment polymer (a) to the fluorine-containing resin (b) is excellent in mechanical properties, heat resistance, mechanical properties at high temperature and abrasion resistance and molded article produced therefrom is useful as a material for various products, for example, a heat resistant material for OA equipment, particularly rolls and belts for OA equipment. On the other hand a material comprising an unintended fluorine-containing multi-segment polymer having an un-reacted elastomeric fluorine-containing polymer chain segment has an adverse effect on products and parts produced therefrom such as lowering of mechanical strength, heat resistance and abrasion resistance.


Further the present inventors have found that by mixing the fluorine-containing multi-segment polymer (a) to the fluorine-containing resin (b), non-tackiness, particularly easiness of removing a stain is excellent as compared with a mere blend of an elastomeric fluorine-containing polymer and a fluorine-containing resin and a material comprising only a fluorine-containing multi-segment polymer.

The flexible fluorine-containing material of the present

invention can be given a good flexibility by the elastomeric segment A contained in the fluorine-containing multi-segment polymer (a) to be used. Particularly when using for rolls and belts for OA equipment, it is preferable that an elastic modulus of the whole flexible fluorine-
 5 containing material is not more than 7×10^8 dyn/cm² at 150°C, particularly not more than 5×10^8 dyn/cm² at 150°C, thereby giving a good fixing property and color developing property even in applications for fuser rolls or belts, in which the tendency is toward high quality picture and coloring.

10 Examples of the usable perhaloolefin as a recurring unit of the elastomeric segment A are, for instance, tetrafluoroethylene (TFE), chlorotrifluoroethylene (CTFE), perfluorovinylethers such as perfluoro(alkyl vinyl ether) (alkyl group has 1 to 5 carbon atoms) (PAVE) and

15




wherein Y is F or CF₃, R_f is a perfluoroalkyl group having 1 to 5 carbon atoms, p is 0 or an integer of from 1 to 5, q is 0 or an integer of from 1 to
 20 5, provided that p + q ≥ 1, hexafluoropropylene (HFP), and the like. Among them, those having a combination and composition giving elastomeric property can be used. Further a monomer giving a curing site for peroxide crosslinking, polyol crosslinking, polyamine crosslinking and other curing reaction and a monomer having functional
 25 group for imparting adhesive property, etc. with other material may be introduced in an amount of not more than 10 % by mole.


In the fluorine-containing multi-segment polymer (a) to be

used in the present invention, the elastomeric segment A is a segment which is generally non-crystalline and has a glass transition temperature of not more than 25°C. Examples of the preferred composition thereof are, for instance, 50 to 85/15 to 50/0 to 10 % by mole, particularly 50 to 80/20 to 50/0 to 5 % by mole of TFE/PAVE/monomer giving a curing or adhering function.


Examples of the monomer giving a curing site are, for instance, vinylidene fluoride, $\text{CF}_2=\text{CHI}$, iodine-containing monomers represented by $\text{CX}_2=\text{CX}-\text{R}_f^3\text{CHRI}$, in which X is H, F or CH_3 , R_f^3 is a linear or branched fluoro- or perfluoro-alkylene group or fluoro- or perfluoro-oxyalkylene group which may have at least one ether type oxygen atom, a fluoropolyoxyalkylene group or a perfluoropolyoxyalkylene group, R is H or CH_3 , nitrile-containing monomers represented by:




wherein m is from 0 to 5, n is from 1 to 3,




wherein n is from 1 to 4,



wherein n is from 2 to 5,




5 wherein n is from 1 to 6,



wherein n is from 1 to 2, and

10




wherein X^4 is CN, COOH or COOR^1 , in which R^1 is an alkyl group which
 15 has 1 to 10 carbon atoms and may contain fluorine atom, bromine-
 containing monomers, carboxyl group-containing monomers,
 alkoxycarbonyl group-containing monomers, and the like. Usually the
 iodine-containing monomer, nitrile-containing monomer, carboxyl
 group-containing monomer, or the like is suitable.

20

A suitable iodine-containing monomer is a perfluoro(vinyl
 ether) compound from the viewpoint of its copolymerizability. For
 example, perfluoro(6,6dihydro-6-iodo-3-oxa-1-hexene) and perfluoro(5-
 iodo-3-oxa-1-pentene) are suitable.

Other examples are fluorovinylethers described in JP-B-5-
 25 63482 which are represented by the formula:



wherein Y^3 is a trifluoromethyl group, n is 0 or an integer of 1 to 2, and the like.

Examples of the monomer capable of giving good adhesion to other materials, e.g. metals such as aluminum and stainless steel and
5 organic materials such as silicone rubber and polyimide, are non-fluorine-containing or fluorine-containing monomers having hydroxyl group, carboxyl group, carboxylic acid derivative, sulfonic acid, sulfonic acid derivative, epoxy group, acetyl group or the like.

In order to impart enough flexibility to rolls for OA equipment,
10 particularly a fuser roll and a soft roll of pressure roll, it is preferable that the glass transition temperature of the elastomeric segment A in the fluorine-containing multi-segment polymer of the present invention is not more than 10°C.

The elastomeric segment A can be prepared by iodine
15 transferring polymerization method known as a process for preparing a fluorine-containing rubber (JP-B-58-4728, JP-A-62-12734).

For example, there is a method of carrying out emulsion polymerization with stirring the above-mentioned perhaloolefin and if necessary, a monomer giving a curing site under pressure in water
20 medium substantially under oxygen-free condition in the presence of an iodine compound, preferably a diiodine compound and a radical polymerization initiator.

Representative examples of the diiodine compound to be used are, for instance, 1-3-diiodoperfluoropropane, 1,4-
25 diiodoperfluorobutane, 1,3-diiodo-2-chloroperfluoropropane, 1,5-diiodo-2,4-dichloroperfluoropentane, 1,6-diiodoperfluorohexane, 1,8-diiodoperfluorooctane, 1,12-diiodoperfluorododecane, 1,16-

diiodoperfluorohexadecane, diiodomethane and 1,2-diiodoethane. Those compounds can be used alone or in a mixture thereof. Among them, 1,4-diiodoperfluorobutane is preferred. An amount of the diiodine compound is from 0.01 to 1 % by weight based on the total
5 weight of the elastomeric segment A.

A radical polymerization initiator which is used for preparing the elastomeric segment A of the present invention may be the same as that which has been used for polymerization of a fluorine-containing elastomer. Examples thereof are organic and inorganic peroxides and
10 azo-compounds. Representative examples of the initiator are persulfates, carbonate peroxides, peroxide esters, and the like. Preferred initiator is ammonium persulfate (APS). The APS can be used alone or in combination with a reducing agent such as sulfites.

Though a wide range of emulsifying agents can be used for
15 the emulsion polymerization, from a point of inhibiting a chain transfer reaction with the molecules of the emulsifying agent which occurs during the polymerization, carboxylic acid salts having a fluorocarbon chain or fluoropolyether chain are desirable. An amount of the emulsifying agent is desirably from about 0.05 to about 2 % by weight,
20 particularly desirably from 0.2 to 1.5 % by weight based on added water.

Since the monomer mixture gas used in the present invention is explosive as described in Advances in Chemistry Series, G. H. Kalb et al, 129, 13 (1973), it is necessary to take measures for a polymerization equipment not to cause a sparking. From that point of view, it is
25 preferable that a polymerization pressure is as low as possible.

The polymerization pressure can be changed in a wide range, generally in a range of from 0.5 to 5 MPa. The higher the


polymerization pressure is, the more a polymerization speed increases. Therefore the polymerization pressure is desirably not less than 0.8 MPa from the viewpoint of increasing productivity.

It is preferable that a number average molecular weight of the
5 thus obtained elastomeric segment A is from 5,000 to 750,000, particularly from 20,000 to 400,000 from the viewpoint of imparting flexibility, elasticity and mechanical properties to the whole fluorine-containing multi-segment polymer obtained.

An end of the thus obtained elastomeric segment A is of
10 perhalo type and has an iodine atom which becomes a starting point of block copolymerization of the non-elastomeric segment B.

In the present invention, the non-elastomeric segment B is basically not limited if it has a fluorine atom and does not have the above-mentioned elastomeric property. The non-elastomeric segment
15 B may be selected according to characteristics and functions which are intended to be obtained by block-copolymerizing the non-elastomeric segment B.

Among the monomers constituting the non-elastomeric segment B, examples of the fluorine-containing monomer are, for
20 instance, one or more of perhaloolefins such as TFE, CTFE, PAVE, HFP, $\text{CF}_2=\text{CF}(\text{CF}_2)_p\text{X}^3$ in which p is an integer of from 1 to 10, X^3 is F or Cl, and perfluoro-2-butene; and partly fluorinated olefins such as vinylidene fluoride (VdF), vinyl fluoride, trifluoroethylene,



in which X^1 and X^2 are H or F, q is an integer of from 1 to 10, and

$\text{CH}_2=\text{C}(\text{CF}_3)_2$. Also one or more of monomers copolymerizable therewith, for example, ethylene, propylene, vinyl chloride, vinyl ethers, vinyl esters of carboxylic acid and acryls can be used as copolymerizable components.

5 Among them, from the viewpoint of chemical resistance and heat resistance, a sole use of fluorine-containing olefin, a combination of fluorine-containing olefins, a combination of ethylene and TFE and a combination of ethylene and CTFE are preferable as the monomers to be used as the main components. Particularly a sole use of perhaloolefin
10 and the combination of perhaloolefins are preferable.

Examples thereof are

- (1) VdF/TFE (0 to 100/100 to 0), particularly VdF/TFE (70 to 99/30 to 1), PTFE or PVdF;
 - (2) ethylene/TFE/HFP (6 to 43/40 to 81/10 to 30), 3,3,3-
15 trifluoropropylene-1,2-trifluoromethyl-3,3,3-trifluoropropylene-1/PAVE (40 to 60/60 to 40);
 - (3) TFE/ $\text{CF}_2=\text{CF}-\text{R}_f^1$ (amount exhibiting non-elastomeric property, namely, an amount of $\text{CF}_2=\text{CF}-\text{R}_f^1$ is less than 15 % by mole. R_f^1 is CF_3 or OR_f^2 , in which R_f^2 is a perfluoro alkyl group having 1 to 5 carbon
20 atoms);
 - (4) VdF/TFE/CTFE (50 to 99/30 to 0/20 to 1);
 - (5) VdF/TFE/HFP (60 to 99/30 to 0/10 to 1);
 - (6) ethylene/TFE (30 to 60/70 to 40);
 - (7) polychlorotrifluoroethylene (PCTFE);
 - 25 (8) ethylene/CTFE (30 to 60/70 to 40);
- and the like.

When heat resistance and abrasion resistance are required in

case of a material for fuser rolls and belts in the field of OA equipment, it is preferable that a crystalline melting point of the non-elastomeric segment B is not less than 150°C. In case of a material for fuser rolls and belts particularly for high speed copying machine or printer, the crystalline melting point is particularly preferably not less than 250°C. Particularly from the viewpoint of good heat resistance, non-tackiness and abrasion resistance, the non-elastomeric fluorine-containing polymer chain segment having perhaloolefin as a main recurring unit is preferred.

Further it is particularly preferable that the non-elastomeric segment B in the fluorine-containing multi-segment polymer of the present invention is the polymer chain comprising more than 85 % by mole and not more than 100 % by mole of tetrafluoroethylene and 0 % by mole or less than 15 % by mole of the formula (1) represented by:



wherein R_f^1 is CF_3 or OR_f^2 , in which R_f^2 is a perfluoroalkyl group having 1 to 5 carbon atoms. The resulting polymer exhibits excellent characteristics such as heat resistance, abrasion resistance and non-tackiness against toner in case of use for rolls for OA equipment and fuser rolls.

An iodine atom at a molecular end of the fluorine-containing multi-segment polymer of the present invention can be replaced with another atom or organic group by various methods.

For example, the molecular end of the fluorine-containing multi-segment polymer of the present invention consisting of

perhaloolefin can be fluorinated and replaced with $-CF_3$ group by treating the polymer with a fluorine gas.

Thereby non-tackiness, heat resistance, oil resistance and chemical resistance of the fluorine-containing multi-segment polymer
5 can be enhanced more.

The treatment with fluorine gas is carried out by bringing the fluorine-containing multi-segment polymer of the present invention consisting of perhaloolefin into contact with a fluorine gas usually at 50° to 250°C, preferably at a temperature up to 200°C for 1 to 10
10 hours, preferably for 2 to 5 hours. A treating pressure may be from 1 to 10 kgG/cm², usually an atmospheric pressure. The fluorine gas to be used may be a pure fluorine gas. From the viewpoint of safety, the fluorine gas diluted with an inert gas such as nitrogen gas, helium gas or argon gas to 2 to 25 % by volume, preferably 7 to 15 % by
15 volume is preferred.

When brought into contact with the fluorine gas, the fluorine-containing multi-segment polymer (a) may be in any form of powder, pellet or flake. The polymer can be subjected to fluorination treatment after formed into a film, tube or other molded article.

20 To the non-elastomeric segment B or to the structure of the fluorine-containing multi-segment polymer (a) of the present invention, if necessary, a carboxyl group or its derivative, hydroxyl group, sulfonic acid group or its derivative, epoxy group or the like can be introduced by copolymerization of a monomer having
25 functional group or by reaction of an end group of the segment polymer, and thereby adhesion to a substrate, crosslinkability and affinity for a filler can be enhanced and various other functions can be

imparted.

Block copolymerization of the non-elastomeric segment B can be carried out subsequently to the emulsion polymerization of the elastomeric segment A by changing a monomer to one for the non-
5 elastomeric segment B.

A number average molecular weight of the non-elastomeric segment B can be adjusted in a wide range of from 1,000 to 1,200,000, preferably from 3,000 to 600,000. An important feature of the present invention is to use the fluorine-containing multi-segment polymer in
10 which the non-elastomeric segment B can be securely block-copolymerized with the elastomeric segment A and the molecular weight (degree of polymerization) of the non-elastomeric segment B can be increased. As mentioned above, this can be achieved by making the elastomeric segment A have perhaloolefin units of not less than 90 % by
15 mole, particularly not less than 95 % by mole as a recurring unit.

The thus obtained fluorine-containing multi-segment polymer (a) mainly comprises polymer molecules (B-A-B) in which the non-elastomeric segments B are bonded to both sides of the elastomeric segment A and polymer molecules (A-B) in which the non-elastomeric
20 segment B is bonded to one side of the elastomeric segment A. An amount of polymer molecules (C) which comprise only the elastomeric segment A without being bonded to the non-elastomeric segment B is not more than 20 % by weight, preferably not more than 10 % by weight based on the total amount of the segment A and polymer molecule (C) in
25 the fluorine-containing multi-segment polymer.

When the polymer having the polymer molecule (C) in an amount exceeding 20 % by weight is mixed to the fluorine-containing

resin (b), mechanical properties and abrasion resistance of products and parts produced therefrom are lowered. Particularly in case of use for a roll and belt for OA equipment which are heated to 150°C or more, an abrasion resistance particularly at high temperature is lowered.

- 5 The proportion of the elastomeric segment A and the non-elastomeric segment B in the fluorine-containing multi-segment polymer (a) of the present invention is optionally selected depending on kind of intended products and parts, for example, rolls and belts for OA equipment, required properties, etc. and also depending on the
10 compositions of each segment. The proportion of the elastomeric segment A to the non-elastomeric segment B is preferably selected in the range of from 5:95 to 99:1 (% by weight). Particularly in case of use as a material for rolls at fixing part where flexibility, heat resistance and abrasion resistance are required, the proportion of the elastomeric
15 segment A to the non-elastomeric segment B is preferably from 20:80 to 98:2 (% by weight), further preferably from 50:50 to 98:2 (% by weight).

- Also in case of use, for example, for rolls and belts of OA equipment, if the proportion of the elastomeric segment A is too small, flexibility becomes insufficient and fixing property and color developing
20 property become insufficient. If the proportion of the non-elastomeric segment B is too small, there is a tendency that heat resistance, mechanical properties at use at high temperatures and abrasion resistance become insufficient. When the proportion of the non-elastomeric segment B is not more than 30 % by weight from the
25 viewpoint of mold-processability, the segment polymer (a) having excellent mold-processability, particularly melt-moldability, melt-extrusion moldability and injection moldability can be provided.

Particularly since the melt-extrusion moldability is excellent, a film or tube having a thickness of as thin as about 10 μm to about 500 μm and a smooth surface can be produced. From this point of view, it is further preferable that the proportion of the segment A to the segment B is from
5 70:30 to 98:2 (% by weight).

When a crosslinking point is provided by introducing a curing site in the elastomeric segment A, vulcanization (crosslinking) can be carried out by peroxide vulcanization with known organic peroxides, polyol vulcanization with known polyols, polyamine
10 vulcanization with known polyvalent amine compounds, and the like.

Also the vulcanization can be carried out by a method of triazine crosslinking by forming a triazine ring with an organotin compound (for example, JP-A-58-152041), a method of oxazole crosslinking by forming an oxazole ring with bisaminophenol similarly
15 by using a fluorine-containing elastomer having a nitrile group introduced as a crosslinking point (for example, JP-A-59-109546), a method of imidazole crosslinking by forming an imidazole ring with a tetraamine compound (for example, JP-A-59-109546) and a method of thiazole crosslinking by forming a thiazole ring with bisaminothiophenol
20 (for example, JP-A-8-104789), or the like method.

Next, the fluorine-containing resin as the component (b) is explained below. The fluorine-containing resin (b) is naturally a substance different from the above-mentioned fluorine-containing multi-segment polymer (a).

25 The fluorine-containing resin (b) has a crystalline melting point or glass transition temperature of not less than 150°C and possesses an ability of improving heat resistance and particularly

mechanical properties at high temperatures without lowering the excellent non-tackiness and mechanical properties of the fluorine-containing multi-segment polymer (a).

The fluorine-containing resin is selected from those mentioned above depending on purpose and application of the flexible material of the present invention. When the flexible material is used as a surface material and molding material such as rolls of OA-related equipment, sealing materials for automotive-related parts and sealing materials for semiconductor producing equipment, the crystalline melting point or glass transition temperature thereof is not less than 150°C, more preferably not less than 250°C.

Among the fluorine-containing resins, perfluoro fluorine-containing resins having excellent heat resistance, non-tackiness, chemical resistance and friction property and capable of giving such properties to the flexible fluorine-containing material, particularly one or more of PTFE, PFA, FEP and EPA are preferable.

In the flexible fluorine-containing material of the present invention, the preferable weight ratio (a)/(b) of the component (a) to the component (b) can be selected in a wide range of from 1/99 to 99/1. Particularly in order to maintain flexibility sufficiently and provide mechanical properties and heat resistance, the weight ratio is 20/80 or more, particularly 30/70 or more, 40/60 to 99/1, 50/50 to 90/10, particularly 80/20 or less.

A combination of the fluorine-containing multi-segment polymer (a) and the fluorine-containing resin (b) is optionally selected. Particularly a selection of the fluorine-containing resin (b) having the same or similar components as those of the non-elastomeric segment B

in the fluorine-containing multi-segment polymer (a) is preferable from the viewpoint of excellent compatibility between the both components.

For example, the following combinations are preferable.

A composition comprising:

- 5 (a) Fluorine-containing multi-segment polymer
Segment A: TFE/PAVE (PAVE: 30 to 50 % by mole) copolymer
Segment B: TFE/PAVE (PAVE: 0.5 to 5 % by mole) copolymer

(b) Fluorine-containing resin

PFA,

- 10 A composition comprising:

(a) Fluorine-containing multi-segment polymer

Segment A: TFE/PAVE copolymer

Segment B: TFE/HFP copolymer

(b) Fluorine-containing resin

- 15 FEP,

A composition comprising:

(a) Fluorine-containing multi-segment polymer

Segment A: TFE/PAVE copolymer

Segment B: TFE homopolymer

- 20 (b) Fluorine-containing resin

A resin selected from PTFE, PFA, FEP and EPA, and

A composition comprising:

(a) Fluorine-containing multi-segment polymer

Segment A: TFE/PAVE copolymer

- 25 Segment B: TFE/HFP/PAVE copolymer

(b) Fluorine-containing resin

A resin selected from EPA, PFA and FEP.

In case of the composition mainly comprising, for example, the fluorine-containing multi-segment polymer (a) and the fluorine-containing resin (b) (for example, PTFE or PTFE copolymer) which cannot be melt-molded, mixing thereof may be carried out by usual method of mixing PTFE containing a filler. The flexible fluorine-containing material of the present invention can be obtained by mixing with a mixer, for example, a tumbler mixer, Henschel mixer, or the like and is used as a molding material for compression molding, etc. In case of the composition mainly comprising the fluorine-containing multi-segment polymer (a) and the fluorine-containing resin (b) (for example, PFA, FEP, EPA, or the like) which are melt-moldable, melt-mixing is preferable. Examples of the melt-mixing equipment are a mixing roll, Banbury mixer, Brabender mixer, extruder and the like. Among them, the extruder is preferable from the points that a kneading power is larger and enhancement of a dispersibility can be expected more at blending the fluorine-containing multi-segment polymer (a) and the fluorine-containing resin (b) and that a productivity for producing the material is good. For mixing, the extruder having a single screw or two or more screws can be used, and particularly a two-screw extruder is preferred because a kneading power is large, thereby making it possible to obtain a composition having a good dispersibility and a kneading power can be controlled optionally.

The composition is generally formed into a pellet by the melt-mixing and is used as a molding material for melt-extrusion molding into a tube or film and injection molding. Further the composition is pulverized and can be used as a coating material.

To the flexible fluorine-containing material of the present

invention can be mixed various fillers depending on purpose and applications.

Particularly when the flexible fluorine-containing material of the present invention is used as a material for rolls and belts of OA equipment which are represented by fuser rolls of a copying machine, printer, etc., fillers which can impart electric conductivity to the roll surface are mixed mainly.

Examples of the filler for imparting electric conductivity are carbon blacks (Ketjen Black, Acetylene Black, etc.); carbons such as PAN type carbon fiber, pitch type carbon fiber and pulverized expansive graphite; fluorinated carbons obtained by completely or partly fluorinating those carbons; metals such as Ag, Ni, Cu, brass, silver-plated copper, Zn, Al and stainless steel (in the form of powder, flake, fiber or the like); metal oxides in the form of fine particles such as SnO_2 (Sb dope), In_2O_3 (Sn dope) and ZnO (Al dope); ferrites; highly dielectric substances such as barium titanate; and the like.

An adding amount of the filler capable of imparting electric conductivity is optionally selected depending on a desired surface resistance or volume specific resistance of rolls or belts for OA equipment and further depending on kind of an electrically conductive filler to be used. The adding amount is from about 0.1 to 40 % by weight, preferably from 1 to 30 % by weight based on the whole composition comprising the flexible fluorine-containing material of the present invention and the filler.

Particularly a partly fluorinated carbon is preferred from the points that the resistance can be controlled stably in a narrow range of from 10^8 to 10^{13} Ωcm and that electric conductivity can be

given without lowering non-tackiness of the fluorine-containing polymer.

Examples of the preferred partly fluorinated carbon are those obtained by fluorinating carbon materials such as carbon black, carbon fiber, petroleum coke and graphite powder.

Among them, preferred is a fluorinated carbon black obtained by fluorinating carbon black, particularly a fluorinated carbon black having a ratio F/C of fluorine atom to carbon atom of not less than 0.1 and less than 1.0, particularly not less than 0.1 and less than 0.5.

If the F/C of the fluorinated carbon black is less than 0.1, an effect of the fluorination is insufficient and problems which a carbon material before the fluorination possesses remain unsolved, namely a problem that a ratio of change in resistance for an adding amount is very large and controlling of electric conductivity is difficult and a problem that dispersing of fluorinated carbon black becomes non-uniform due to a developed structure and the obtained composition becomes hard. If the F/C is not less than 1.0, a desired electric conductivity cannot be given to the composition.

The F/C is measured by the method mentioned below. The fluorinated carbon black is wrapped together with a combustion improver Na_2O_2 and a polyethylene film with a filtrating paper, and burnt in a tightly closed flask filled with oxygen. Hydrogen fluoride generated is measured by a usual method by using a fluoride ion meter (Ion Analyzer 901 available from Orion Co., Ltd.). A fluorine content is calculated from the obtained value. Then the F/C is calculated from the obtained fluorine content.

The fluorinated carbon black mainly comprises a poly(carbon monofluoride). Preferred is a fluorinated carbon black obtained by fluorinating a carbon black having an average particle size of from 0.01 to 50 μm , preferably from 0.01 to 1 μm with a fluorine gas. In case of a
5 fluorinated carbon black obtained by using a carbon material having an average particle size exceeding 50 μm , for example, petroleum coke, graphite powder, carbon fiber, or the like as a starting material, an adding amount thereof has to be increased for imparting electric conductivity and non-tackiness to the resin, and disadvantages tend to
10 arise, such as an increase in a surface roughness of the obtained composition, lowering of mechanical strength and non-uniform resistance.

The carbon materials suitable for the fluorinated carbon black are carbon blacks having an average article size in the above-
15 mentioned range. Carbon blacks which can be used are those commercially available, for example, Furnace Black for rubber (for example, ASAHI #55 available from Asahi Carbon Co., Ltd., etc.), Channel Black for coloring (for example, LEBEN 7000 available from Columbia Carbon Co., Ltd.), Thermal Black (SEVACARBON MT-C1
20 available from Columbia Carbon Co., Ltd.), and the like.

Among the carbon blacks, particularly those generally called an electrically conductive carbon black are preferred. The electrically conductive carbon blacks are those defined by factors such as a smaller average particle size (not more than 0.1 μm), a large surface area (N_2
25 surface area: 50 m^2/g or more), a developed structure (oil absorption: 100 cc/g or more), a less content of impurities (ash content: less than 0.1 %) and an advanced graphitization, and are widely used because

even a relatively small amount thereof can impart electric conductivity to the material. Examples of the commercially available electrically conductive carbon black are, for instance, Ketjen Black EC and Ketjen Black EC-600JD (available from Ketjen Black International Co., Ltd.),
5 Black Pearls 2000, Vulcan XC-72 and CSX-99 (available from Cablack Co., Ltd.), Denca Black (available from Denki Kagaku Kogyo Kabushiki Kaisha), Conductex 950 (available from Columbia Carbon Co., Ltd.), and the like.

The fluorinated carbon black can be obtained by contacting
10 the above-mentioned carbon materials with a fluorine gas at a temperature within a range of from 200° to 600°C, preferably from 300° to 500°C. In a reaction temperature range lower than the mentioned range, there occur the problems that a progress of the fluorination reaction is slow, a degree of the fluorination is hardly increased, a
15 thermal stability is not sufficient and the properties inherent to the fluorinated carbon black such as non-tackiness and lubricity are not exhibited. On the contrary, in a reaction temperature range higher than the mentioned range, a thermal cracking reaction easily arises and a yield of an obtained fluorinated carbon black is decreased. Also there
20 is a case where a sudden thermal cracking occurs, resulting in an explosion. Therefore attention must be paid to that.

The fluorine gas to be used for the reaction may be diluted with an inert gas such as nitrogen, argon, helium, carbon tetrafluoride, or the like or may contain hydrogen fluoride. The reaction can be
25 carried out under normal pressure, and even if the reaction is carried out under reduced pressure or under pressure, there is no problem.

Besides the above-mentioned conditions, a reaction time, a

fluorine gas flow, etc. may be optionally adjusted depending on a reactivity of the starting carbon material with fluorine and a desired F/C value (fluorine content).

The proportion of the fluorine-containing multi-segment polymer of the present invention to the fluorinated carbon is optionally selected depending on a desired resistance, and is from 1/99 to 20/80 (weight ratio, hereinafter the same). If an amount of the fluorinated carbon black becomes small, an effect of the addition thereof is not sufficiently obtained, and if the amount becomes too large, there is a tendency that a mechanical strength such as a tensile strength is lowered.

Further a filler for enhancing mechanical properties and compression restoration property may be mixed to the composition. Typical examples of the preferable filler are fibrous fillers such as a glass fiber, carbon fiber, asbestos fiber and potassium titanate fiber.

Examples of rolls for OA equipment, to which the flexible fluorine-containing material of the present invention having heat resistance and non-tackiness is applied, are as follows.

Roll Example 1

- (i) Metallic core roll of aluminum or stainless steel
- (ii) Fluorine-containing material of the present invention which comprises 40 to 99 % by weight of the fluorine-containing multi-segment polymer (a) comprising, as the elastomeric segment A, not less than 75 % by weight of one or more segments comprising a polymer chain having a molecular weight of 5,000 to 750,000 and obtained by copolymerizing 50 to 85 % by mole of tetrafluoroethylene with 15 to 50 % by mole of perfluoro(alkyl vinyl ether) and as the

non-elastomeric segment B, 25 % by weight of one or more segments comprising a polymer chain having a molecular weight of 3,000 to 1,200,000 and obtained by polymerizing more than 85 % by mole and not more than 100 % by mole of tetrafluoroethylene with 0 % by mole
5 or less than 15 % by mole of the formula (1):



wherein R_f^1 is CF_3 or $-\text{OR}_f^2$, in which R_f^2 is a perfluoroalkyl group having
10 1 to 5 carbon atoms, and 1 to 60 % by weight of the fluorine-containing resin (b), preferably a perfluoro polymer having a crystalline melting point or glass transition temperature of not less than 150°C.

Fuser roll or pressure roll at a fixing part which is produced by laminating (ii) as an outer layer of (i).

15 Roll Example 2

(i) Metallic core roll of aluminum or stainless steel

(ii) Composition prepared by mixing a filler capable of imparting electric conductivity to the fluorine-containing multi-segment polymer described in (ii) (outer layer) of Roll Example 1

20 Fuser roll or pressure roll at a fixing part which is produced by laminating (ii) as an outer layer of (i).

The fluorine-containing material of the present invention itself has flexibility and therefore even if laminated directly on the metallic core roll as described in the above-mentioned Roll Examples
25 1 and 2, enough flexibility can be obtained. In addition, by providing an elastic layer of silicone rubber, fluorine-containing rubber, urethane rubber, EPDM or the like, the roll can be endowed with more

flexibility and effectively comply with requirements for higher quality picture and paper feeding property at high speed. Among them, the elastic layers having a rubber hardness of 10 to 40 degrees or not more than 10 degrees (including a layer in the form of sponge) are selected.

Roll Example 3

(i) Metallic core roll of aluminum or stainless steel

(ii) Silicone rubber

(iii) Flexible fluorine-containing material described in (ii) (outer layer)

10 of Roll Example 1

Fuser roll or pressure roll at a fixing part which is produced by laminating the silicone rubber layer (ii) on the core roll (i) and thereon the layer (iii) as an outermost layer.

Roll Example 4

15 (i) Metallic core roll of aluminum or stainless steel

(ii) Silicone rubber

(iii) Composition prepared by mixing a filler capable of imparting electric conductivity to the fluorine-containing material described in (ii) (outer layer) of Roll Example 1

20 Fuser roll or pressure roll at a fixing part which is produced by laminating the silicone rubber layer (ii) on the core roll (i) and thereon the layer (iii) as an outermost layer.

Between each layer of each layered roll of the above-mentioned Roll Examples 1 to 4, an adhesive or primer may be used to improve adhesion thereof.

Preferred are Roll Examples 3 and 4. Usually any one of the fuser roll or pressure roll of the fixing part or the both of them are

provided with a heating device such as a ceramic heater to soften or melt a toner for fixing an image to a paper. The material of the present invention has enough heat resistance against such a heating device.

5 The flexible fluorine-containing material of the present invention is used as a molding material which can be molded into the form of sheet, film or tube and thus is applied on the roll or belt for OA equipment. In that case, known molding methods can be used. The fluorine-containing multi-segment polymer or the composition
10 prepared by blending a filler to the fluorine-containing multi-segment polymer can be molded into necessary forms by extrusion molding, injection molding, compression molding or the like.

 Further the flexible fluorine-containing material of the present invention can be used as a coating material when prepared
15 into a composition containing a liquid carrier or into a powder form having a specific particle size and apparent density. The coating material can be used not only for application in OA equipment but also for a lining material, roll, belt, hose, sealing material, and the like in the fields of transportation such as automobiles,
20 semiconductor production facilities, chemical plant, aircraft, food processing facilities, photographic and printing facilities, coating apparatuses, steel making facilities, etc. The coating material comprises the above-mentioned fluorine-containing multi-segment polymer (a) and the fluorine-containing resin (b). As the fluorine-
25 containing multi-segment polymer (a) and the fluorine-containing resin (b), those described above in the heat resistant material for OA equipment having flexibility can be preferably used similarly. The

coating material is applied on the rolls and belts for OA equipment and substrates in other applications and a coating film having excellent flexibility, sealing property, heat resistance, abrasion resistance and non-tackiness can be obtained.

5 Further the flexible fluorine-containing material of the present invention can be applied on the coating powder. For the coating powder, the same material as the above-mentioned heat resistant material for OA equipment having flexibility can be preferably used. The coating powder which is used preferably is in
10 the form of powder or particle having a particle size of from 10 to 1,000 μm and an apparent density of from 0.3 to 1.2 g/cc.

To the coating powder can be optionally added additives, for example, a pigment such as a carbon powder, titanium oxide or cobalt oxide; a reinforcing material such as a glass fiber powder,
15 carbon fiber powder or mica; an amine type anti-oxidant, organic sulfuric compound, organotin type anti-oxidant, phenolic anti-oxidant or a thermal stabilizer such as metal soap; a leveling agent; an anti-static agent; the same filler as mentioned above which is capable of imparting electric conductivity; and the like in the range
20 not lowering remarkably characteristics of the fluorine-containing resin such as heat resistance.

Mixing of the coating powder to the above-mentioned additives may be carried out in the form of powder (dry type) or in the form of slurry (wet type). Preferred is the mixing in the form of powder.
25 Examples of the usable mixing equipment are, for instance, usual mixers such as a sand mill, V-type blender and ribbon type blender and pulverizing machine.

The coating powder is generally coated through electrostatic coating, fluid bed dipping, rotary lining or the like and then baked (preferably at a temperature of not less than a crystalline melting point thereof) to form a good coating film.

- 5 Generally it is possible to form a coating film of from 10 to 200 μm thick in case of the electrostatic powder coating and from 200 to 1,000 μm thick in case of the rotary lining.

10 The flexible fluorine-containing material of the present invention can be formed into a coating composition by mixing to a liquid medium. For the coating composition, the same flexible fluorine-containing materials as those for the above-mentioned heat resistant material for OA equipment having flexibility can be preferably used.

15 The liquid carrier to be used for the coating composition is selected from liquids which can dissolve or disperse the fluorine-containing multi-segment polymer (a) and the fluorine-containing resin (b) constituting the flexible fluorine-containing material of the present invention. Examples thereof are alcohols such as methanol, ethanol, propanol and butanol and in addition, hydrocarbon type solvents
20 such as acetone, methyl ethyl ketone, ethyl acetate, dimethylformamide, dimethylacetamide, N-methyl-2-pyrrolidone, dimethylsulfoxide, triethylphosphate, tetrahydrofuran, methyl isobutyl ketone, cyclohexanone, 1,4-dioxane, methyl cellosolve acetate, 2-nitropropane, methyl isoamyl ketone, 4-methoxy-4-
25 methylpentanone-2 and 4-methoxy-4-methylpentanol-2; haloalkanes such as trichlorotrifluoroethane, dichlorotetrafluoroethane, dichlorodifluoroethane, chlorodifluoroethane,

dichloropentafluoropropane, tetrachlorohexafluorobutane and perfluorohexane; fluorine-containing solvents such as fluorine-containing ethers, i.e. FLORINATE FC-75 (available from Three M Co., Ltd.), FLORINATE FC-77 (available from Three M Co., Ltd.) and
5 HFE7100 (available from Three M Co., Ltd.); water; and a mixture of two or more thereof.

Also it is possible to blend usual additives such as a pigment, surfactant, anti-foaming agent, viscosity control agent and leveling agent in the range not lowering remarkably heat resistance, chemical
10 resistance, non-tackiness and abrasion resistance.

Besides the additives, a coupling agent can be used as another component to enhance adhesive property.

The coupling agent means a compound which acts on an interface between the organic material and the inorganic material and
15 forms a strong bridge between the both materials through chemical or physical coupling. The coupling agent is usually a compound of silicone, titanium, zirconium, hafnium, trium, tin, aluminum or magnesium which has a group capable of coupling the organic material and the inorganic material. Among those coupling agents, preferred
20 are a silane coupling agent, ortho-acid esters of transition elements (for example, titanium or zirconium) of the group IV in Periodic Table and derivatives thereof, and particularly preferred is an amino silane compound.

The coating composition can be in the form of aqueous
25 dispersion, organic solvent dispersion, organosol or aqueous emulsion of organosol containing the flexible fluorine-containing material of the present invention and if necessary, the above-mentioned additives.

Among them, the form of aqueous dispersion for a coating is preferred from environmental and safety point of view. Particularly preferred is the composition in the state of the fluorine-containing multi-segment polymer being dispersed in water in the form of fine particles of from
5 0.01 to 1.0 μm , in which a surfactant is generally blended for stabilizing the dispersion.

The aqueous dispersion for a coating can be prepared through various processes. Concretely there are, for example, a process for finely pulverizing a powder of fluorine-containing multi-
10 segment polymer obtained by suspension polymerization, or the like, mixing the finely pulverized powder to the fluorine-containing resin powder and then dispersing the mixture uniformly in an aqueous medium with a surfactant, a process for preparing an aqueous dispersion of fluorine-containing multi-segment polymer at the same
15 time of polymerization by emulsion polymerization, mixing, thereto, the fluorine-containing resin fine powder or an aqueous dispersion of fluorine-containing resin obtained by emulsion polymerization and if necessary, adding a surfactant and additives, and the like process. From the viewpoint of productivity and quality (for forming into smaller
20 and uniform particle size), the process for preparing the aqueous dispersions of both the fluorine-containing multi-segment polymer (a) and the fluorine-containing resin (b) directly through the emulsion polymerization and then mixing the both dispersions is preferred.

A method of coating of the coating composition is optionally
25 selected depending on kind of the fluorine-containing multi-segment polymer, form of a coating, purpose and application. For example, in case of the aqueous dispersion and organic solvent dispersion, usually

spray coating, brush coating, roll coating and spin coating are carried out. After the coating, drying and sintering are carried out to give a coating film on a substrate. The sintering conditions are optionally selected depending on kind (composition, melting point, etc.) of the
5 fluorine-containing multi-segment polymer (a) and the fluorine-containing resin (b). Generally the sintering is carried out at a temperature of not less than the melting point of the non-elastomeric segment B in the fluorine-containing multi-segment polymer (a) and not less than the melting point of the fluorine-containing resin (b). The
10 sintering time is from five minutes to three hours, preferably from about 10 minutes to about 30 minutes while it varies depending on the sintering temperature.

Such a coating material is coated on a metallic core roll (aluminum and SUS) of a roll as a heat resistant material for OA
15 equipment having flexibility in the same manner as mentioned above or on an elastic layer of silicone rubber, fluorine-containing rubber, urethane rubber or EPDM provided on the core roll, and thus a fuser roll or pressure roll having not only flexibility, heat resistance and abrasion resistance but also excellent non-tackiness and oil resistance can be
20 obtained.

In order to obtain the above-mentioned rolls for OA equipment by applying the coating material, after applying, if necessary, a primer to the metallic core roll or intermediate elastic layer and then sintering depending on necessity, it is possible to coat any of the
25 aqueous dispersion coating, solvent-soluble coating, solvent-dispersion coating or powder coating comprising the coating material of the present invention by the above-mentioned method and then sinter at a

temperature of not less than a melting point thereof to form a coating film. The thickness of the coating film varies depending on purpose, application and hardness of a substrate, and is selected in the range of from 1 to 500 μm , preferably from 5 to 150 μm , particularly from 5 to 100 μm . If necessary, the coating film may be ground to make its surface smooth. It is preferable to adjust a surface roughness (Ra) to not more than 2.0 μm , more preferably not more than 1.0 μm .

Also there is another method of producing rolls for OA equipment, that is, a method of producing a tube from the flexible fluorine-containing material of the present invention and covering a metallic core roll with the obtained tube. The tube is a cylindrical article obtained by molding the flexible fluorine-containing material into a tubular form. The above-exemplified flexible fluorine-containing material can be preferably used similarly.

A size of the tube varies depending on purpose, application and method of use, and is not limited. There is usually used a tube having an inner diameter of about 5 to 50 mm and a thickness of not more than 1 mm. Particularly in case of rolls for OA equipment such as fuser rolls and pressure rolls, the inner diameter and thickness are preferably from 10 to 40 mm and from 0.01 to 0.15 μm , respectively.

The tube is formed into a tube by usual melt-extrusion. The tube may be stretched (single screw or two screws) if necessary and may have thermal shrinkability, but usually may have neither stretchability nor thermal shrinkability.

The tube may contain the above-mentioned filler imparting electric conductivity if necessary. The tube can be produced usually by mixing previously an electric conductivity-imparting agent by kneading

or dry blending to the starting material (in the form of pellet or powder) before molding into the tube by melt-extrusion.

The molding method is also not limited particularly. Generally melt extrusion molding with a ring die is carried out as mentioned above. Namely a cylindrical film melt-extruded through a ring die with a single screw or multi-screw extruder is taken off while being cooled as it is with a proper cooling means or is taken off while adjusting its size and shape toward inside or outside by using a sizing jig after the ring die and cooling at normal temperature or with a coolant such as air or water. In that case, there is no restriction in employing such conditions as feeding of air into the cylindrical article, stretching somewhat at the time of taking off and carrying out slow cooling or rapid cooling.

The tube usually comprises one layer, and may comprise two or more layers. In such a case, it is necessary to study enough and select compatibility between polymers of each layer and a heating temperature under specific conditions mentioned below. This is because a heat treating temperature of each layer differs from each other. Molding is carried out by co-extrusion method, and there are no specific conditions like the molding of one layer.

The tube is optionally subjected to inner surface treatment, if necessary, in order to enhance adhesion to an article to be covered with the tube. Example of the preferred inner surface treatment is chemical etching treatment, and for example, sodium-based etching agent is used preferably. In addition to the chemical etching, any of inner surface treatments may be employed as far as enhancement of adhesion can be expected. Further after the chemical etching of the inner surface, a

primer may be applied to enhance adhesion to a substrate more.

The tube produced by using the material of the present invention is used for rolls (particularly for fuser roll and pressure roll) for OA equipment and can impart excellent flexibility and heat resistance to
5 the rolls. In addition to those characteristics, good non-tackiness can be given by fitting the tube on an outermost surface of the roll.

The roll provided with the tube may be produced as mentioned above by covering its metallic core roll directly with the tube or by providing an elastic layer of silicone rubber, fluorine-containing
10 rubber, urethane rubber or EPDM between the metallic core roll and the tube.

While the tube can impart enough flexibility to the roll surface even if covered directly on the metallic core roll, more flexibility can be given to the roll surface by providing the elastic layer between the
15 core roll and the tube, and in case of use as a fuser roll and pressure roll for OA equipment, a higher quality picture and enhanced paper feeding property at high speed can be attained. In that case, an elastic layer having a rubber hardness of from about 10 degrees to about 30 degrees or an elastic layer having a rubber hardness of not more than 10 degrees
20 (including a layer in the form of sponge) is preferred.

If necessary, an adhesive is used or treatment with a primer is carried out to impart adhesion between the tube and the substrate (metallic core roll or elastic layer) contacting thereto. In that case, it is preferable to use the above-mentioned tube subjected to the inner
25 surface treatment by etching from the point that a stronger adhesion can be obtained.

In producing the roll by providing the tube directly on the

metallic core roll, known methods can be optionally employed. It is preferable that a tube having thermal shrinkability and subjected to etching treatment of its inner surface is covered on a metallic core roll subjected to primer treatment and is shrunk at a temperature of not
5 more than a melting point (for example, at 150° to 200°C) for setting to the substrate, followed by sintering at a temperature of not less than the melting point (for example, at 320° to 400°C) to bond by fusion.

The roll having an elastic layer between the tube and the metallic core roll can be produced by a method of firstly putting the
10 metallic core roll and the tube in a cylindrical molded article so that a space is provided between the core roll and the tube and the inner surface of the cylindrical molded article comes into contact with the outer surface of the tube, and then pouring a raw rubber, latex or elastomer into the above-mentioned space, and if necessary carrying out
15 vulcanizing. It is a matter of course that the roll covered with the tube has to be taken out of the cylindrical molded article at a necessary time. In that case, the inner surface of the tube may be previously subjected to etching treatment or primer treatment so that it is easily contacted to the rubber portion. Also a rubber roll may be produced previously and
20 then covered with the tube on the surface of the rubber roll. In that case, it is better to use a tube having thermal shrinkability. Thus there is no restriction in the production method of the roll.

When the roll obtained above is used as rolls for OA equipment such as a fuser roll and pressure roll, a step for making the
25 surface of roll smooth may be carried out as the case demands.

For example, a surface roughness (Ra) of the roll can be decreased by grinding the roll surface. Preferred Ra is not more than 2

μm , more preferably not more than $1.0 \mu\text{m}$.

Further the flexible fluorine-containing material of the present invention can be used in various applications other than the application for OA equipment, by making use of its heat resistance, chemical resistance, non-tackiness, flexibility, sealing property and abrasion resistance. Examples of the application are shown in Tables 1, 2 and 3.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211

TABLE 1

Field of industry	Sub-field of industry	Final product	Equipment
Electrical	Semi-conductor	Semi-conductor production apparatus	CVD equipment
		Liquid crystal panel production apparatus	Dry etching equipment
		Plasma panel production apparatus	Wet etching equipment
			Oxidation and diffusion equipment
			Sputtering equipment
Transportation	Vehicle		Ashing equipment
			Cleaning equipment
			Ion implantation equipment
			Engine and auxiliary equipment
			AT
			Fuel line and auxiliary equipment
			Fuel line
			Fuel line
			Fuel line
			- continued -

- continued -	
	Parts
O (square) ring, packing, sealing material, tube, roll	
Coating, lining, gasket, diaphragm, hose	
Gasket, shaft seal, valve stem seal, sealing material, hose	
Hose, sealing material	
O (square) ring, tube, packing, core material of valve, hose, sealing material, diaphragm	
Diaphragm, O (square) ring, valve, tube, packing, hose, sealing material	
ditto	
ditto	
- continued -	

- continued -		
Chemical	Chemical products	Plant
		Production line of chemicals such as pharmaceutical, agricultural chemical, coating and resin
		(Petroleum)
	Chemicals	Pharmaceuticals
		Plug for chemicals
Mechanical	Photograph	Developing machine
		Film developing machine
		X-ray film developing machine
	Printing	Printing machine
		Printing roll
	Coating	Coating facilities
		Coating roll
	Analyzer and physical and chemical appliances	
Food	Plant	Food processing line
Metal	Steel making	Steel sheet processing facilities
		Steel sheet processing roll
- continued -		

- continued -

Lining, valve, packing, roll, hose, diaphragm, O (square) ring, tube, sealing material

Plug for chemicals

Roll

Roll

Roll

Roll

Tube

Lining, valve, packing, roll, hose, diaphragm, O (square) ring, tube, sealing material

Roll

TABLE 2

Field of Industry	Characteristics Required
Electrical	Plasma resistance, acid resistance, alkali resistance, amine resistance, ozone resistance, gas resistance, chemical resistance, cleanliness, heat resistance
Transportation	Heat resistance, amine resistance
	Heat resistance, amine resistance
	Fuel resistance, fuel permeability, heat resistance
	Fuel resistance, fuel permeability, heat resistance
	Fuel resistance, fuel permeability, heat resistance
	Fuel resistance, fuel permeability, heat resistance

- continued -

- continued -

Chemical	Chemical resistance, solvent resistance, heat resistance
	Chemical resistance, solvent resistance, heat resistance
	Cleanliness
Mechanical	Chemical resistance
	Chemical resistance
	Solvent resistance
	Solvent resistance
Food	Chemical resistance, solvent resistance, heat resistance
Metal	Heat resistance, acid resistance

TABLE 3

Field of industry	Parts
Electrical	O ring and sealing material for gate valve of corresponding product or equipment
	O ring and sealing material for quartz window of corresponding product or equipment
	O ring and sealing material for chamber of corresponding product or equipment
	O ring and sealing material for gate of corresponding product or equipment
	O ring and sealing material for bell jar of corresponding product or equipment
	O ring and sealing material for coupling of corresponding product or equipment
	O ring and sealing material for pump of corresponding product or equipment
	O ring and sealing material for gas controller for semi-conductor of corresponding product or equipment
	O ring and sealing material for resist developing and releasing solutions
	O ring and sealing material for wafer cleaning solution
	Diaphragm of pump for corresponding production equipment
	Hose for resist developing and releasing solutions
	Hose and tube for wafer cleaning solution
	Roll for transferring wafer
	Lining and coating of tanks for resist developing and releasing solutions
	Lining and coating of tanks for wafer cleaning solution
	Lining and coating of tanks for wet etching

- continued -

- continued -

Transportation Engine head gasket

Metal gasket

Crank shaft seal

Cam shaft seal

Valve stem seal

Manifold packing

Oil hose

ATF hose

Injector O ring

Injector packing

O ring and diaphragm for fuel pump

Fuel hose

- continued -

- continued -	
Chemical	
Mechanical	Developing roll
	Developing roll
	Gravure roll
	Guide roll
	Gravure roll for magnetic tape production and coating line
	Guide roll for magnetic tape production and coating line
	Various coating rolls
Food	
Metal	

The present invention is then explained based on examples and preparation examples but is not limited to those examples.

PREPARATION EXAMPLE 1

5 (Preparation of fluorine-containing multi-segment polymer)

Synthesis of elastomeric segment A

A 47-liter stainless steel autoclave having no ignition source was charged with 30 liters of pure water, 300 g of $C_7F_{15}COONH_4$ as an emulsifying agent and 2.7 g of disodium hydrogenphosphate $12H_2O$ as a
10 pH control agent, and after the inside of a system was sufficiently replaced with nitrogen gas, the autoclave was heated up to $50^\circ C$ with stirring at 200 rpm and a gas mixture of TFE and perfluoro(methyl vinyl ether) (PMVE) (32/68 in mole ratio) was introduced (780 g of a monomer mixture) so that the inside pressure became $8.0 \text{ kgf/cm}^2\text{G}$. Then 100
15 ml of an aqueous solution of ammonium persulfate (APS) having a concentration of 37.2 mg/ml was fed with pressurized nitrogen gas to initiate a reaction.

At the time when the inside pressure lowered down to $7.0 \text{ kgf/cm}^2\text{G}$ with advance of the polymerization, 18.21 g of diiodine
20 compound $I(CF_2)_4I$ and 234 g of an aqueous solution of 10 % by weight of $C_7F_{15}COONH_4$ were introduced with pressurized nitrogen gas. Then 60 g of TFE was fed with self-pressure thereof and 58 g of PMVE was fed under pressure with a plunger pump (TFE/PMVE=63/37 in mole ratio) so that the pressure became $8.0 \text{ kgf/cm}^2\text{G}$. Thereafter TFE and PMVE
25 were fed in the same manner under pressure with the advance of the reaction, and thus increasing and lowering of the pressure were repeated between $7 \text{ kgf/cm}^2\text{G}$ and $8 \text{ kgf/cm}^2\text{G}$.

When a total charging amount of TFE and PMVE reached 5,900 g twelve hours after starting of the polymerization reaction, the autoclave was cooled and un-reacted monomers were released to obtain an aqueous dispersion having a solid content of 16.0 % by weight.

5 A part of the aqueous dispersion was sampled, frozen, coagulated and thawed, followed by washing a coagulated product with water and then vacuum-drying to obtain a rubber-like polymer. A Mooney viscosity ML_{1+10} (140°C) of the polymer was 58.

10 As a result of ^{19}F -NMR analysis, monomer components of the polymer were TFE/PMVE=61/39 % by mole, and T_g (center value) measured according to DSC analysis was 2°C.

Block copolymerization with non-elastomeric segment B

15 The same 47-liter stainless steel autoclave as above was charged with 3,200 g of the aqueous dispersion obtained above, 142 g of perfluoro(propyl vinyl ether) (PPVE) and 400 g of pure water. After replacing the inside of a system was sufficiently replaced with nitrogen gas, the inside temperature was kept at 50°C. With stirring at 120 rpm, tetrafluoroethylene was introduced under pressure so that the inside pressure became 5.5 kgf/cm²G (amount of tetrafluoroethylene: 400 g).

20 Then a solution prepared by dissolving 0.4 g of ammonium persulfate in 50 ml of water was introduced with pressurized nitrogen gas to initiate a reaction.

 Since the inside pressure lowered down with the advance of the polymerization reaction, at the time when it lowered to 5.0 kgf/cm²G, 25 it was again raised with a tetrafluoroethylene gas up to 5.5 kgf/cm²G, and thus increasing and lowering of the pressure were repeated.

 At the time when 950 g of tetrafluoroethylene was consumed

after starting of the polymerization, supplying thereof was stopped, the autoclave was cooled and un-reacted monomers were released to obtain 6,000 g of a semi-transparent aqueous dispersion.

The polymer content of the obtained aqueous dispersion was
5 18.3 % by weight, and the particle size thereof measured by dynamic light scattering method was 58 nm.

The proportion of the non-elastomeric fluorine-containing polymer chain segment B to the whole polymer which was calculated from an increase in yield of the polymer, namely, ((Yield of polymer
10 obtained in post polymerization) - (Amount of polymer charged)) ÷ (Yield of polymer obtained in post polymerization) × 100 was 17 % by weight.

The obtained aqueous dispersion was frozen and coagulated, and the precipitated polymer was washed and dried to obtain a white solid.

15 The white solid powder was charged in an electric oven maintained at 230°C, and the inside of the oven was replaced with nitrogen gas, followed by flowing of 20 % by volume of fluorine gas (nitrogen gas: 80 % by volume) at a rate of 0.5 liter/min for five hours. After that, the inside of the oven was sufficiently replaced with nitrogen
20 gas and the oven was cooled to obtain a fluorinated fluorine-containing multi-segment polymer (white powder).

According to ¹⁹F-NMR analysis, components of the non-elastomeric fluorine-containing polymer chain segment B in the obtained fluorine-containing multi-segment polymer was
25 TFE/PPVE=98/2 % by mole. Also according to DSC analysis, the glass transition temperature of the elastomeric fluorine-containing polymer chain was 2°C and the crystalline melting point of the non-elastomeric

fluorine-containing polymer chain segment was 282°C. The melt flow rate measured under conditions of preheating at 372°C for five minutes at a load of 5 kgf/cm² by using Koka-type flow tester and nozzles of 2 mm diameter × 8 mm length was 4.9 g/10 min.

5

PREPARATION EXAMPLE 2

(Preparation of fluorine-containing multi-segment polymer)

Synthesis of elastomeric segment A

A 47-liter stainless steel autoclave having no ignition source
10 was charged with 30 liters of pure water, 300 g of C₇F₁₅COONH₄ as an emulsifying agent and 2.7 g of disodium hydrogenphosphate·12H₂O as a pH control agent, and after the inside of a system was sufficiently replaced with nitrogen gas, the autoclave was heated up to 50°C with stirring at 200 rpm and a gas mixture of TFE/PMVE (32/68 in mole
15 ratio) was introduced so that the inside pressure became 8.0 kgf/cm²G (monomer mixture: 787 g). Then 100 ml of an aqueous solution of ammonium persulfate (APS) having a concentration of 68.6 mg/ml was fed with pressurized nitrogen gas to initiate a reaction.

At the time when the inside pressure lowered down to 7.0
20 kgf/cm²G with the advance of the polymerization, 27.2 g of diiodine compound I(CF₂)₄I and 234 g of an aqueous solution of 10 % by weight of C₇F₁₅COONH₄ were introduced with pressurized nitrogen gas. Then 60 g of TFE was fed with self-pressure thereof and 58 g of PMVE was fed under pressure with a plunger pump (TFE/PMVE=63/37 in mole ratio)
25 so that the pressure became 8.0 kgf/cm²G. Thereafter TFE and PMVE were fed in the same manner under pressure with the advance of the reaction, and thus increasing and lowering of the pressure were

repeated between 7 kgf/cm²G and 8 kgf/cm²G.

When the total charging amount of TFE and PMVE reached 6,000 g sixteen hours after starting of the polymerization reaction, the autoclave was cooled and un-reacted monomers were released to obtain
5 an aqueous dispersion having the solid content of 16.6 % by weight.

A part of the aqueous dispersion was sampled, frozen, coagulated and thawed, followed by washing a coagulated product with water and then vacuum-drying to obtain a rubber-like polymer. The Mooney viscosity ML₁₊₁₀ (100°C) of the polymer was 59 and the Mooney
10 viscosity ML₁₊₁₀ (140°C) of the polymer was 12.

As a result of ¹⁹F-NMR analysis, monomer components of the polymer were TFE/PMVE=64/36 % by mole, and Tg (center value) measured according to DSC analysis was 3°C.

Block copolymerization with non-elastomeric segment B

15 The same 47-liter stainless steel autoclave as above was charged with 1,840 g of the aqueous dispersion obtained above, 208 g of perfluoro(propyl vinyl ether) (PPVE) and 1,200 g of pure water. After the inside of a system was sufficiently replaced with nitrogen gas, the inside temperature was kept at 50°C. With stirring at 120 rpm,
20 tetrafluoroethylene was introduced under pressure so that the inside pressure became 5.5 kgf/cm²G (amount of tetrafluoroethylene: 640 g).

Then the solution prepared by dissolving 0.27 g of ammonium persulfate in 50 ml of water was introduced with pressurized nitrogen gas to initiate a reaction.

25 Since the inside pressure lowered down with the advance of the polymerization reaction, at the time when it lowered to 5.0 kgf/cm²G, it was again raised with a tetrafluoroethylene gas up to 5.5 kgf/cm²G,

and thus increasing and lowering of the pressure were repeated.

At the time when 1,400 g of tetrafluoroethylene was consumed after starting of the polymerization, supplying thereof was stopped, the autoclave was cooled and un-reacted monomers were released to obtain 4,000 g of a semi-transparent aqueous dispersion.

The polymer content of the obtained aqueous dispersion was 21.0 % by weight, and the particle size thereof measured by dynamic light scattering method was 59 nm.

The proportion of the non-elastomeric fluorine-containing polymer chain segment B to the whole polymer which was calculated from an increase in yield of the polymer, namely, $((\text{Yield of polymer obtained in post polymerization}) - (\text{Amount of polymer charged})) \div (\text{Yield of polymer obtained in post polymerization}) \times 100$ was 33 % by weight.

The obtained aqueous dispersion was frozen and coagulated, and the precipitated polymer was washed and dried to obtain a white solid.

The white solid powder was charged in an electric oven maintained at 230°C, and the inside of the oven was replaced with nitrogen gas, followed by flowing of 20 % by volume of fluorine gas (nitrogen gas: 80 % by volume) at a rate of 0.5 liter/min for five hours. After that, the inside of the oven was replaced with nitrogen gas sufficiently and the oven was cooled to obtain a fluorinated fluorine-containing multi-segment polymer (white powder).

According to ^{19}F -NMR analysis, components of the non-elastomeric fluorine-containing polymer chain segment in the obtained fluorine-containing multi-segment polymer was TFE/PPVE=98/2 % by mole. Also according to DSC analysis, the glass transition temperature

of the elastomeric fluorine-containing polymer chain was 3°C and the crystalline melting point of the non-elastomeric fluorine-containing polymer chain segment was 297°C. The melt flow rate measured under conditions of preheating at 372°C for five minutes at a load of 5 kgf/cm² by using Koka-type flow tester and nozzles of 2 mm diameter × 8 mm length was 3.5 g/10 min.

EXAMPLE 1

The white solid of fluorine-containing multi-segment polymer prepared in Preparation Example 1 and PFA (NEOFLON PFA AP201 available from DAIKIN INDUSTRIES, LTD. and having a crystalline melting point of 302°C) were dry-blended in a weight ratio of 80/20 and kneaded at 350°C with a two-screw extruder (LABOPLASTOMILL available from TOYO SEIKI KABUSHIKI KAISHA), followed by extruding to obtain a flexible fluorine-containing material of the present invention in the form of pellets.

The obtained pellets were put in a 100 mm diameter metal die which was then set on a press machine set at 350°C, followed by preheating for 30 minutes and then compression-molding at 70 kg/cm² for one minute to obtain an about 0.5 mm thick film.

The following physical properties of the obtained film were measured. The results are shown in Table 4.

(Mechanical properties)

Tensile strength: The film is cut to a form of dumbbell described in ASTM-1467, and measurements are carried out at a cross head speed of 200 mm/min by using a TENSILON universal tester available from Orientec Corporation.

Elastic modulus: The film is cut to a form of dumbbell described in ASTM-1467, and measurements are carried out at a cross head speed of 200 mm/min by using a TENSILON universal tester available from Orientec Corporation.

- 5 Rubber hardness: Hardness A is measured according to JIS K 6301.

Resin hardness: Hardness D is measured according to JIS K 7215.

(Viscoelasticity)

- 10 The film is cut to a form of strip of about 35 × 5 mm and set on a viscoelasticity meter RSA-2 available from Rheometric Co., Ltd. Then a viscoelasticity is measured at a frequency of 1 Hz at 150°C and 200°C.

(Mold-processability)

- 15 A melt flow rate is measured under conditions of preheating at 372°C for five minutes at a load of 5 kgf/cm² by using Koka-type flow tester (CFT-500C available from Shimadzu Corporation) and nozzles of 2 mm diameter × 8 mm length.

(Surface characteristics)

- 20 Water contact angle: A water contact angle on the film surface is measured at room temperature by using a contact angle meter.

- Contact angle of 31 dyne solution: A solution (31 dyne solution) having a surface tension of 31 dyne/cm is prepared by mixing 25 97.5 (v/v %) of ethylene glycol and 2.5 (v/v %) of formaldehyde. A contact angle of 31 dyne solution is measured by using a contact angle meter.

(Non-tackiness)

Tackiness: The same two films are overlapped with each other and pressed at a load of 10 kgf for one minute. Then the films are separated. Tackiness is evaluated by a feeling of stickiness at separating. Criteria for judgement are represented by ◎ when the films are separated spontaneously when the load is released; ○ when the films can be separated and peeled off by hands; and × when the films cannot be separated or are broken when peeled off.

Stain-proofing property: Five lines of 3 cm long are drawn on the film with a commercially available oily ink (black), and after air-drying for 60 seconds, the surface of the film is rubbed by ten turns with a 500 g metallic disc (50 mm diameter) with a commercially available gauze stuck on a flat bottom surface thereof. The evaluation is indicated by × when the lines remain un-erased after the rubbing by ten turns and ○ when no lines remain.

EXAMPLES 2 to 3

A flexible fluorine-containing material of the present invention was produced in the same manner as in Example 1 except that the mixing ratio of the fluorine-containing multi-segment polymer (a) to PFA (b) was changed as shown in Table 4, and each physical property was evaluated in the same manner as in Example 1. The results are shown in Table 4.

EXAMPLE 4

A flexible fluorine-containing material of the present invention was produced in the same manner as in Example 1 except that

the polymer prepared in Preparation Example 2 was used as the fluorine-containing multi-segment polymer (a), and each physical property was evaluated in the same manner as in Example 1. The results are shown in Table 4.

5

EXAMPLE 5

A flexible fluorine-containing material of the present invention was produced in the same manner as in Example 2 except that FEP (NEOFLON FEP NP20 available from DAIKIN INDUSTRIES, LTD.)
10 was used as the fluorine-containing resin (b) instead of PFA, and a film was produced. Each physical property was evaluated in the same manner as in Example 1. The results are shown in Table 4.

TABLE 4

	Ex. 1	Ex. 2	Ex. 3	Ex. 4	Ex. 5
Fluorine-containing material					
Fluorine-containing multi-segment polymer (a)					
Elastomeric segment A (% by mole)	TFE/PMVE (61/39)	TFE/PMVE (61/39)	TFE/PMVE (61/39)	TFE/PMVE (64/36)	TFE/PMVE (61/39)
Non-elastomeric segment B (% by mole)	TFE/PPVE (98/2)	TFE/PPVE (98/2)	TFE/PPVE (98/2)	TFE/PPVE (98/2)	TFE/PPVE (98/2)
Proportion of B in (a) (% by weight)	17	17	17	33	17
Fluorine-containing resin (b)	PFA	PFA	PFA	PFA	FEP
(a)/(b) (weight ratio)	80/20	60/40	20/80	80/20	60/40

- continued -

Properties of material						
Mechanical properties						
Tensile strength (kg/cm ²)	101	118	173	112	105	
Elastic modulus (kg/cm ²)	152	189	212	168	145	
Rubber hardness (ASTR-A)	54	64	85	58	59	
Resin hardness	22	25	44	23	23	
Viscoelasticity						
150°C-E' (107 dyn/cm ²)	6.50	6.70	6.80	6.55	6.2	
200°C-E' (107 dyn/cm ²)	4.10	5.80	5.60	4.30	3.9	
Mold-processability (MFL: 372°C, 5 kgf)	5.5	7.9	11.9	4.1	6.8	
Surface characteristics						
Water contact angle (degree)	110	114	112	112	113	
Contact angle of 31 dyne solution (degree)	58	61	57	59	60	
Non-tackiness						
Tackiness	○	○	○	○	○	
Stain-proofing property	○	○	○	○	○	

COMPARATIVE EXAMPLE 1

A fluorine-containing material for comparison was produced in the same manner as in Example 1 except that PFA was not mixed, and each physical property was evaluated in the same manner as in Example

5 1. The results are shown in Table 5.

COMPARATIVE EXAMPLE 2

A fluorine-containing material for comparison was produced in the same manner as in Example 4 except that PFA was not mixed, and
10 each physical property was evaluated in the same manner as in Example

1. The results are shown in Table 5.

COMPARATIVE EXAMPLE 3

A film was produced in the same manner as in Example 1
15 except that PFA (same one as in Example 1) was used alone without using a fluorine-containing multi-segment polymer, and each physical property was evaluated in the same manner as in Example 1. The results are shown in Table 5.

COMPARATIVE EXAMPLE 4

20 A fluorine-containing material for comparison was produced in the same manner as in Example 1 except that 67 parts by weight of a polymer prepared by fluorinating, in the same manner as in Preparation Example 1, the elastomeric polymer (a polymer before copolymerizing a
25 non-elastomeric segment, TFE/PMVE = 61/39 (mole ratio)) prepared in Preparation Example 1 and 33 parts by weight of PFA were used, and each physical property was evaluated in the same manner as in Example

1. The results are shown in Table 5.

THE **NEW** **YORK** **PUBLIC** **LIBRARY**

TABLE 5

	Com. Ex. 1	Com. Ex. 2	Com. Ex. 3	Com. Ex. 4
Fluorine-containing material				
Fluorine-containing multi-segment polymer (a)				
Elastomeric segment A (% by mole)	TFE/PMVE (61/39)	TFE/PMVE (64/36)	-	TFE/PMVE (61/39)
Non-elastomeric segment B (% by mole)	TFE/PPVE (98/2)	TFE/PPVE (98/2)	-	-
Proportion of B in (a) (% by weight)	17	33	-	0
Fluorine-containing resin (b)	-	-	PFA	PFA
(a)/(b) (weight ratio)	100/0	100/0	0/100	67/23

- continued -

- continued -

Properties of material				
Mechanical properties				
Tensile strength (kg/cm ²)	77	95	277	35
Elastic modulus (kg/cm ²)	49	143	420	240
Rubber hardness (ASTR-A)	48	56	>95	74
Resin hardness	20	23	60	40
Viscoelasticity				
150°C-E' (107 dyn/cm ²)	3.10	6.50	88.0	2.80
200°C-E' (107 dyn/cm ²)	1.20	4.60	48.0	0.35
Mold-processability (MFI: 372°C, 5 kgf)	4.9	3.5	18.6	15
Surface characteristics				
Water contact angle (degree)	106	108	110	98
Contact angle of 31 dyne solution (degree)	53	55	55	51
Non-tackiness				
Tackiness	x	x	◎	x
Stain-proofing property	x	x	○	x

INDUSTRIAL APPLICABILITY

As it is clear from the results of Table 4 and 5, in case where the fluorine-containing resin (PFA) is not mixed (Comparative Examples 1 and 2), non-tackiness (particularly stain removability) is inferior, and
5 in case of a sole use of the fluorine-containing resin (PFA) (Comparative Example 3), the material does not have a flexibility at all. Also in case of the mixture comprising PFA and the fluorine-containing polymer which is not copolymerized with the non-elastomeric segment (Comparative Example 4), not only a mechanical strength is inferior but also
10 mechanical properties are suddenly lowered at high temperature and non-tackiness is inferior. On the other hand, the flexible fluorine-containing material of the present invention can provide various products, particularly products and parts for OA equipment which are excellent in flexibility, mechanical strength, viscoelasticity (heat
15 resistance) and mold-processability and have improved non-tackiness (particularly stain removability).

CLAIMS

1. A flexible fluorine-containing material which comprises (a)
a fluorine-containing multi-segment polymer having an elastomeric
5 fluorine-containing polymer chain segment A and a non-elastomeric
fluorine-containing polymer chain segment B in which the elastomeric
fluorine-containing polymer chain segment A comprises not less than
90 % by mole of a perhaloolefin unit and (b) a fluorine-containing resin
having a crystalline melting point or glass transition temperature of not
10 less than 150°C, in which a weight ratio (a)/(b) is 1/99 to 99/1.

2. The flexible fluorine-containing material of Claim 1,
wherein said fluorine-containing resin (b) has a crystalline melting point
or glass transition temperature of not less than 250°C.
15

3. The flexible fluorine-containing material of Claim 1 or 2,
wherein said weight ratio (a)/(b) is 20/80 to 99/1.

4. The flexible fluorine-containing material of any of Claims 1
20 to 3, wherein the elastomeric fluorine-containing polymer chain segment
A contained in the fluorine-containing multi-segment polymer (a) is
non-crystalline and has a glass transition temperature of not more than
25°C.

25 5. The flexible fluorine-containing material of any of Claims 1
to 4, wherein the non-elastomeric fluorine-containing polymer chain
segment B contained in the fluorine-containing multi-segment polymer

(a) is a polymer chain having a crystalline melting point or glass transition temperature of not less than 150°C.

6. The flexible fluorine-containing material of Claim 5,
5 wherein the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is a polymer chain having a crystalline melting point or glass transition temperature of not less than 250°C.

10 7. The flexible fluorine-containing material of any of Claims 1 to 6, wherein the elastomeric fluorine-containing polymer chain segment A contained in the fluorine-containing multi-segment polymer (a) is a polymer chain comprising 50 to 85 % by mole of tetrafluoroethylene and 15 to 50 % by mole of perfluoro(alkyl vinyl ether) and/or
15 hexafluoropropylene.

8. The flexible fluorine-containing material of any of Claims 1 to 7, wherein the non-elastomeric fluorine-containing polymer chain segment B contained in the fluorine-containing multi-segment polymer
20 (a) is a polymer chain comprising more than 85 % by mole and not more than 100 % by mole of tetrafluoroethylene and 0 % by mole or less than 15 % by mole of a compound of the formula (1):



25

wherein R_f^1 is CF_3 or OR_f^2 , in which R_f^2 is a perfluoroalkyl group having 1 to 5 carbon atoms.

9. The flexible fluorine-containing material of any of Claims 1 to 8, wherein the fluorine-containing resin (b) is one or more members selected from perfluoro fluorine-containing resins.

5 10. The flexible fluorine-containing material of Claim 9, wherein the fluorine-containing resin (b) is one or more members selected from polytetrafluoroethylene, tetrafluoroethylene/perfluoro(alkyl vinyl ether) copolymer, tetrafluoroethylene/hexafluoropropylene copolymer and
10 tetrafluoroethylene/hexafluoropropylene/perfluoro(alkyl vinyl ether) copolymer.

11. The flexible fluorine-containing material of any of Claims 1 to 10, wherein a proportion of the non-elastomeric fluorine-containing
15 polymer chain segment B contained in the fluorine-containing multi-segment polymer (a) is not more than 25 % by weight based on the whole segment polymer (a).

ABSTRACT

To provide the fluorine-containing material which is capable of giving various products, particularly products and parts for OA equipment, is excellent in flexibility, mechanical strength, viscoelasticity and mold-processability and possesses improved non-tackiness. The flexible fluorine-containing material comprises (a) the fluorine-containing multi-segment polymer having the elastomeric fluorine-containing polymer chain segment A and the non-elastomeric fluorine-containing polymer chain segment B in which the elastomeric fluorine-containing polymer chain segment A comprises not less than 90 % by mole of a perhaloolefin unit and (b) the fluorine-containing resin having a crystalline melting point or glass transition temperature of not less than 150°C, in which a weight ratio (a)/(b) is 1/99 to 99/1.

Declaration and Power of Attorney for Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下々の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

FLEXIBLE FLUORINE-CONTAINING MATERIAL

HAVING HEAT RESISTANCE AND

NON-TACKINESS

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日 に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
（該当する場合） _____ に訂正されました。

☒ was filed on June 22, 2000
as U.S. Application No. or PCT International
Application No. PCT/JP00/04078
and was amended on _____
(if applicable)

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

Japanese Language Declaration

日本語宣言書

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している。本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

I hereby claim foreign priority under Title 35, United States Code, § 119(a)-(d) or § 365 (b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior foreign application(s)
外国での先行出願

Priority Claimed
優先権の主張

186792/1999 (Number) (番号)	Japan (Country) (国名)
_____ (Number) (番号)	_____ (Country) (国名)
_____ (Number) (番号)	_____ (Country) (国名)

30/6/1999 (Day/Month/Year Filed) (出願年月日)	<input checked="" type="checkbox"/> <input type="checkbox"/> Yes No ありなし
_____ (Day/Month/Year Filed) (出願年月日)	<input type="checkbox"/> <input type="checkbox"/> Yes No ありなし
_____ (Day/Month/Year Filed) (出願年月日)	<input type="checkbox"/> <input type="checkbox"/> Yes No ありなし

私、第35編米国法典119条(e)項に基づいて下記の米国外の特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below.

_____ (Application No.) (出願番号)	_____ (Filing Date) (出願日)
--------------------------------------	---------------------------------

_____ (Application No.) (出願番号)	_____ (Filing Date) (出願日)
--------------------------------------	---------------------------------

私は、下記の米国法典第35編120条に基づいて下記の米国外の特許出願に記載された権利、又は米国外を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外の特許出願に開示されていない限り、その先行米国外出願を提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

_____ (Application No.) (出願番号)	_____ (Filing Date) (出願日)
--------------------------------------	---------------------------------

_____ (Status)(patented, pending, abandoned) (現況：特許許可済、係属中、放棄済)

_____ (Application No.) (出願番号)	_____ (Filing Date) (出願日)
--------------------------------------	---------------------------------

_____ (Status)(patented, pending, abandoned) (現況：特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行えば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration

日本語宣言書

委任状： 私は下記の発明者として、本出願に関する一切の
手続を米特許商標局に対して遂行する弁理士または代理人
として、下記の者を指名いたします。（弁理士、または代理
人の氏名及び登録番号を明記のこと）

POWER OF ATTORNEY: As a named inventor, I hereby
appoint the following attorney(s) and/or agent(s) to prosecute
this application and transact all business in the Patent and
Trademark Office connected therewith: (list name and
registration number)

John H. Mion, Reg. No. 18,879; Thomas J. Macpeak, Reg. No. 19,292; Robert J. Seas, Jr., Reg. No. 21,092; Darryl
Mexic, Reg. No. 23,063; Robert V. Sloan, Reg. No. 22,775; Peter D. Olexy, Reg. No. 24,513; J. Frank Osha, Reg. No.
24,625; Waddell A. Biggart, Reg. No. 24,864; Louis Gubinsky, Reg. No. 24,835; Neil B. Siegel, Reg. No. 25,200;
David J. Cushing, Reg. No. 28,703; John R. Inge, Reg. No. 26,916; Joseph J. Ruch, Jr., Reg. No. 26,577; Sheldon I.
Landsman, Reg. No. 25,430; Richard C. Turner, Reg. No. 29,710; Howard L. Bernstein, Reg. No. 25,665; Alan J.
Kasper, Reg. No. 25,426; Kenneth J. Burchfiel, Reg. No. 31,333; Gordon Kit, Reg. No. 30,764; Susan J. Mack, Reg.
No. 30,951; Frank L. Bernstein, Reg. No. 31,484; Mark Boland, Reg. No. 32,197; William H. Mandir, Reg. No. 32,156;
Brian W. Hannon, Reg. No. 32,778; Abraham J. Rosner, Reg. No. 33,276; Bruce E. Kramer, Reg. No. 33,725; Paul F.
Neils, Reg. No. 33,102; Brett S. Sylvester, Reg. No. 32,765; Robert M. Masters, Reg. No. 35,603; George F. Lehnigk,
Reg. No. 36,359; John T. Callahan, Reg. No. 32,607 and Steven M. Gruskin, Reg. No. 36,848.

書類送付先

Send Correspondence to:
SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC
2100 Pennsylvania Avenue, N.W. Suite 800
Washington, D.C. 20037-3213

直接電話連絡先：（名前及び電話番号）

Direct Telephone Calls to:

(202)293-7060

第一または第一発明者名	Full name of sole or first inventor Takayuki ARAKI
発明者の署名 日付	Inventor's signature 16/11/2001 Date Takayuki Araki
住所	Residence Settsu-shi, OSAKA 566-8585 JAPAN JPX
国籍	Citizenship Japanese
私書箱	Post Office Address c/o Yodogawa-seisakusho, DAIKIN INDUSTRIES, LTD., 1-1, Nishihitotsuya, Settsu-shi, OSAKA 566-8585 JAPAN
第二共同発明者	Full name of second joint inventor, if any Nobuhiro HIRANO
第二共同発明者 日付	Second inventor's signature Date Nobuhiro Hirano 16/11/2001
住所	Residence Settsu-shi, OSAKA 566-8585 JAPAN JPX
国籍	Citizenship Japanese
私書箱	Post Office Address c/o Yodogawa-seisakusho, DAIKIN INDUSTRIES, LTD., 1-1, Nishihitotsuya, Settsu-shi, OSAKA 566-8585 JAPAN

（第三以降の共同発明者についても同様に記載し、署名をする
こと）

(Supply similar information and signature for third and
subsequent joint inventors.)

Japanese Language Declaration

日本語宣言書

第三の共同発明者の氏名 (該当する場合)		Full name of third joint inventor, if any	
同第三発明者の署名	日付	Noritoshi OKA	
住所		Third inventor's signature	Date
国籍		Noritoshi Oka	16/11/2001
郵便の宛先		Residence: Settsu-shi, OSAKA 566-8585 JAPAN JPV	
		Citizenship Japanese	
		Post office address c/o Yodogawa-seisakusho, DAIKIN INDUSTRIES, LTD., 1-1, Nishihitotsuya, Settsu-shi, OSAKA 566-8585 JAPAN	
第四の共同発明者の氏名 (該当する場合)		Full name of fourth joint inventor, if any	
同第四発明者の署名	日付	Fourth inventor's signature	
住所		Date	
国籍		Residence	
郵便の宛先		Citizenship	
		Post office address	
第五の共同発明者の氏名 (該当する場合)		Full name of fifth joint inventor, if any	
同第五発明者の署名	日付	Fifth inventor's signature	
住所		Date	
国籍		Residence	
郵便の宛先		Citizenship	
		Post office address	
第六の共同発明者の氏名 (該当する場合)		Full name of sixth joint inventor, if any	
同第六発明者の署名	日付	Sixth inventor's signature	
住所		Date	
国籍		Residence	
郵便の宛先		Citizenship	
		Post office address	